

equipment

	HD09VXE	HD12VXE	HD17VXE	HD18V5
SUPPORT FRAME				
Rubber tracks (width mm)	180	200	230	230
Attachment points for lifting-anchoring-towing and lubrication of the tilt cylinder foot	std	std	std	std
Expandable undercarriage (mm) - Filling blade with extensions	720-950	870-1135	980-1300	990-1300
Steel tracks (width mm)	-	-	230 opt	-
ENGINE				
Two-phase dry air filter with visual clogging indicator	std	std	std	std
Electric pre-heating device	std	std	std	std
Fuel water separator	std	std	std	std
Plastic fuel tank with drain plug	std	std	std	plastic material
Engine speed adjustment	std	std	std	std
ELECTRICAL SYSTEM				
12V battery with fuse box	std	std	std	std
DRIVING SEAT				
Longitudinal adjustment bucket seat, vinyl covering	std	std	std	std
Non-slip rubber mat	std	std	std	std
Wrist support	-	std	std	std
Seatbelt	with reel	with reel	std	with reel
High speed control	std	std	std	std
Travel control pedals	-	std	std	-
INSTRUMENTS AND CONTROL DEVICES				
Worklight switch; auxiliary system control	std	std	std	std
Aux. system proportional control switch on joystick	-	-	-	std
Water temperature control instrument	-	digital	analogue	analogue
Fuel level control instrument	visual	digital	analogue	analogue
Hour meter	std	std	std	std
Warning light for: pre-heating, engine oil pressure, battery charge, water temperature	std	std	std	std
High gear indicator light	-	-	-	std
Engine alarm device in case of overheating or low oil pressure	std	std	std	std
Travel alarm	-	-	-	opt
CANOPY				
FOPS protection against falling objects	-	opt	std	std
TOPS protection against tipping	-	std	-	-
TOPS and ROPS protection against tipping and rolling	opt	-	std	std
HYDRAULIC SYSTEM				
ISO assisted hydraulic controls	mechanical	std	std	std
Gear pump / variable flow rate (std)	gear	std	std	std
Hydraulic arm swing control	pedal	joystick	pedal	pedal
Track adjustment control	std	std	std	std
Worklight positioned centrally under the arm	-	-	-	std
DIGGING AND MOVING EQUIPMENT				
Monobloc arm (length mm)	1350	1480	1650	1710
Rocker arm (length mm)	700	870	950	-
Long rocker arm	+200 mm (opt)	-	+250 mm (opt)	+250 mm (opt)
Arm hydraulic swinging angle	140°	130°	135°	70° / 55°
Limit shock absorber on boom cylinder	std	std	std	std
Anti-Shock valve on arm cylinder	-	std	std	-
Rapid attachment of mechanical accessories	opt	opt	opt	opt
Bucket in various dimensions	opt	opt	opt	opt
HYDRAULIC CIRCUITS FOR ACCESSORIES				
Hydraulic circuit for hammer with direct return to tank for double-acting accessories	std	std	std	std
Second hydraulic circuit for double-acting accessories	-	-	-	opt
SAFETY AND COMFORT				
Operating and travel controls lock out to enable the operator to exit	std	std	std	std
Single key for ignition, diesel tank cap and bonnet locks	std	std	std	std
Diesel tank cap with lock and mesh filter	-	std	std	std
Glass breaker hammer in the cabin	-	-	-	-
Turret lock automatic brake	std	std	std	std
Boom cylinder anti-drift system	-	-	std	std
Horn	std	std	std	std
External rear counterweight	-	-	opt	opt